

United States Patent [19]

[54] THROMBOLYSIS CATHETER SYSTEM

Mische et al.

[56]

4,610,662 9/1986

4,692.139 9/1987

4,808,153 2/1989

1/1987

4,636,195

[11] Patent Number: 5,279,546

[45] Date of Patent: Jan. 18, 1994

f7		
[75]	Inventors:	Hans A. Mische, St. Cloud, Minn.; Liberato A. Iannone, Des Moines, Iowa
[73]	Assignee:	Lake Region Manufacturing Company, Inc., Chaska, Minn.
[21]	Appl. No.:	927,934
[22]	Filed:	Aug. 7, 1992
	Relat	ted U.S. Application Data
[63]	Continuation of Ser. No. 544,582, Jun. 27, 1990, abandoned.	
[58]	Field of Sea	606/194; 604/101 arch

References Cited

U.S. PATENT DOCUMENTS

4,274,423 6/1981 Mizuno et al. 128/675

Weikl et al. 604/101

Wolinsky 604/101

Stiles 604/19

Parisi 606/159

4,870,953 10/1989 Don Michael et al. 606/159

Primary Examiner—C. Fred Rosenbaum Assistant Examiner-Michael Rafa

Attorney, Agent, or Firm-Grady J. Frenchlick

ABSTRACT

An apparatus and method for dissolving and removing material which tends to occlude a body passage way, such as an artery. The device employs a dual catheter system arranged in coaxial fashion. Each of the catheters has an inflatable balloon at its distal tip. Inflating the two balloons occludes the body passage way both proximal and distal to the treatment area, thus isolating it from fluid contact with the rest of the body. Because concentric catheters are used, the distance between the balloons and hence the size of the treatment area is adjustable. The thrombolytic agent is infused through orifices in the inner catheter in the region between the two balloons. A piezo electric device supplies ultrasonic agitation within the treatment area. A pressure device monitors the body passage way for unsafe conditions. Aspiration is accomplished through one or more lumens in the outer catheter. Ultrasonic agitation may be employed with the aspiration also to break up masses of material which may be too big to pass through the exit lumen cross section.

12 Claims, 9 Drawing Sheets

